

GD-ML-AP2830UHD

71 cm (28") 4K UHD LCD/TFT Monitor LED Backlight 16:9



- Ultra High Definition (UHD) TFT-LCD monitor
- LED Backpanel illumination
- Designed for professional 24/7 usage
- Built-in Speaker
- Metal cabinet



PROFESSIONAL

- Product Line Professional: These products cover most applications of modern video systems

Specifications GD-ML-AP2830UHD

Monitor

LCD Panel size:	71 cm (28") Diagonal AM-TFT LED Backlight
Pixels - Total:	3840 (H) x 2160 (V)
Pixel Pitch:	0.16 mm (H) x 0.16 mm (V)
Aspect Ratio:	16 : 9
Viewing Angle:	170° (H) ~ 160° (V)

Video

Video Standard:	PAL, NTSC
Video Inputs:	1x Display Port, 1x HDMI, 1x VGA, 1x BNC Composite (1Vpp)
Brightness:	250 cd, m ²
Contrast Ratio:	1,000:1
Number of Colours:	16.7 million
Response Time:	5 ms

General

Speakers:	2 x 5 W
OSD (On Screen Display):	Yes, multi language
Accessories included:	Table stand bracket, power adapter, HDMI cable and remote control

I/O Interface

Video Outputs:	1 Vpp, BNC
Audio Inputs:	1x 3.5mm jack (Line) , 1x HDMI

Approvals

Regulation:	CE, EAC, FCC, RoHS Compliant
MTBF at 25° C:	> 100, 000 hours

Environmental

Humidity:	less than 90%, non condensing
Operating Temperature:	0 °C ~ +40 °C

Electrical

Supply Voltage:	100 ~ 240 VAC, 50Hz / 60Hz
Power Consumption:	Max. 40 W

Mechanical

Vesa Mount:	100 x 100 mm
Dimensions:	445 x 660 x 200 mm (17,5 x 26 x 7,9 inch)
Weight:	7500 g (16.5 lb)