

GCA-B3326T

1/3" CCD Bullet Camera VF 5~50 mm ICR 42 IR LED 700L ext. adj.



- Smart IR LED Control with adjustable level
- Varifocal Lens: f = 5 - 50 mm, auto iris, external adjustment
- Concealed Cable Management
- Remote Control Interfaces over Coax (Coaxitron)
- Built-in Service Monitor Port & OSD Control Port
- Video Enhancement: BLC, HLC, DNR, DIS
- 15 polygonal Privacy Zone Masking
- Extended Temperature range -25°C ~ +55°C
- Support Dual Power AC24V/DC12V

SUMMARY

Grundig Analogue DSP Cameras

High quality, reliable and effective.

Grundig analogue cameras have been designed and built to the very highest standards. Grundig has selected components which deliver outstanding image quality, including the very best image sensors, lenses and digital signal processors (DSPs). The cameras have been designed for up-to-date surveillance applications, incorporating functionality such as extended dynamic range (optional), motion adaptive digital noise reduction, intelligent video analytics and more.

All the cameras in the Grundig analogue range have unique features in different housings to suit all eventualities. Outdoor options include Bullet cameras with infrared LED and vandal-resistant domes and indoor options include a large range of dome cameras

SPECIFICATIONS

Image Sensor	1/3" CCD Sony 960H Ex-view HAD II
Scanning System	PAL, 50Hz, 625L (V), 2:1 Inter Line Transfer
Pixels - Effective	976(H) x 582(V)
Resolution	650 (H) lines colour, 700 (H) lines b&w
Col/B&W	On/Off/Auto/Ext, IR-cut filter removable (ICR)
Sensitivity Colour	0.8 lux(50IRE)@F1.4(SensUp=0, AGC Off), 0.00001 lux 15IRE (SensUpx512) F1.4
Sensitivity B&W	0 Lux LED IR on
S/N Ratio	>52 dB
Lens Focal Length	5 ~ 50 mm
Viewing Angle	51° ~ 6.5°
Lens Drive Type	Auto iris (DC)
Iris F-Number	F= 1.4 ~ 360
Sens Up	Off ~ x512, auto
Motion Detection	On/ Off/ Sensitivity/ Area setting
Number of Privacy Zones	15 (polygonal method)
High Speed Shutter	1/50 ~ 1/10.000 sec, auto
BLC	On/Off/HLC
ATR WDR	On/Off
Digital Noise Reduction (DNR)	Low/Midlow/Mid/Midhigh/High/Off (2D/3D)
Digital Image Stabilization (DIS)	Off/On
OSD	Yes (DE,EN,ES,FR,RU,PT,JP)
Camera ID	52 character, 2 lines
White Balance	ATW/Push/User1/User2/AntiCR/Manual/Push Lock
Adjustment zoom and focus	External
IR LED	42 pcs.
Optical Wavelength	850 nm
Max. IR Distance	45/70 m (according to scene reflexion)
Protection Rating	IP66
Remote Control	Coaxitron, data on coax cable
Video Outputs	1 CVBS 1 Vpp (BNC) & 1 test monitor out
Accessories included	Multi-Language Manual, Template, Cable for Service Monitor, Screws, screw driver for Zoom and Focus adjustment
Humidity	less than 90%, non condensing
Operating Temperature	-25°C ~ +55°C
Supply Voltage	12 VDC / 24 VAC
Power Consumption	7.8 (LED on) W
Weight	1.14 kg
Dimensions w*h*d	99 x 223.5 mm

DIMENSIONS

