

GCI-G0862F

5 MP 360° Fisheye IP Camera



- 360° field of view
- 5 Megapixels CMOS, Colour/B&W Camera
- IR LEDs integrated
- ONVIF protocol support
- H.264 & MJPEG compression modes (max. 25 fps)
- SD/SDHC memory card slot for alarm and schedule image recording

SUMMARY

Network Cameras

Intelligent, robust and stylish

IP technology greatly increases the effectiveness of video surveillance systems. Grundig has embraced this new technology and incorporated it into an extensive CCTV IP surveillance camera range. The new camera range includes PTZ and anti-vandal domes, for internal and external applications, with traditional box and specialist, compact casing designs also available. Each Grundig IP camera has impressive functionality, meeting every current surveillance requirement.

SPECIFICATIONS

Image Sensor	Progressive Scan CMOS, 5 Megapixel
Pixels - Total	2592 (H) x 1944 (V)
Col/B&W	On/Off/SMART, IR-cut filter removable (ICR)
Sensitivity Colour	0.2 Lux@F2.8
Sensitivity B&W	0.02 Lux@F2.8
Shutter Speed	1 sec to 1/10,000 sec
PTZ Control	digital Pan/Tilt/Zoom
BLC	On/Off
WDR	D-WDR (Digital wide dynamic range)
Digital Noise Reduction (DNR)	Off, 3DNR Low/Middle/High, SPQ+3DNR
Motion Detection	On/ Off/ Sensitivity/ Area setting
Tampering Alarm	On/Off
Privacy zones	5 zones, rectangle
White Balance	ATW, AWB, Manual
Digital Zoom	Yes
Alarm Inputs	1
Alarm Outputs	1
Web Browser	MS Internet Explorer 6.0 (or higher), Firefox, Google Chrome, Safari
Camera ID	20 character
Number of Clients	Up to 20 user
Video Compression	H.264, MJPEG
Video Streaming	Quad stream: max.: H.264+H.264+H.264+H.264 or H.264+H.264+H.264+MJPEG
Video Resolution	2592x1944 (10fps), 2048x1536 (15fps), 1920x1080 (25fps), etc.
Network Protocol	IPv4, IPv6, TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PPPoE, UPnP, IGMP, 802.1X and SNMP
SD memory	supports up to 32 GB capacity of micro SD/SDHC memory
LED Indicator	Power, link, active
Input/Output sockets	Power (Terminal 3-Pin), RJ-45, Micro SD Card Slot, Alarm Terminal 4-Pin (Alarm In 2-Pin, Alarm Out 2-Pin)
Firmware Upgrade	Firmware upgrade by Web Browser
Configuration	Upload & Download configuration on remote PC
Operating Temperature	-10°C ~ +50°C
Humidity	10 ~ 90% no condensation
Regulation	CE, FCC, RoHS Compliant
Supply Voltage	12 VDC / 24 VAC / PoE
Dimensions w*h*d	Ø149 x 47 mm mm

DIMENSIONS

