



EPS-1016

Article number: 211983

PoE Switch, 16x PoE+, 2x RJ45, 2x SFP, 250W, 19" Rack

Main features

Fast Ethernet: 16x 10/100 Base-TX, IEEE 802.3at

Gigabit Ethernet: 2x 10/100/1000 Base-T, 2x Copper/SFP

VLAN, PoE control, Backup/Restore

Port Mirroring, Password protected

Temperature range 0°~45°C

Up to 30W per port, total max. 250W

Web-based Configuration / Management

RSTP/Loop protection, Bandwidth control

Status LED: Link/PoE

Specifications

Management	yes
VLAN	yes
Ports	16x 10/100Base-TX, 2x 10/100/1000Base-T, 2x SFP Combo-Port
Optical connection	Duplex LC System plug
Ethernet interface	10Base-T, 100Base-TX, 1000Base-T
Switch data rate	10Mbps port - 14,880pps, 100Mbps port - 148,880pps, 1000Mbps port - 1,148,880pps
Support standards	IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX, IEEE 802.3ab 1000BaseT, IEEE 802.3z 1000BaseSX/LX, IEEE 802.3x Flow Control, IEEE 802.3ad Link Aggregation Control Protocol, IEEE 802.1Q VLAN, IEEE 802.1p Class of Service, IEEE 802.1D Spanning Tree Protocol, IEEE
Supply voltage	100~240VAC
Power over Ethernet	yes

EPS-1016

Specifications continued

Power over Ethernet	IEEE 802.3at
Number PoE ports	16
PoE Power	250 W
Model	housing
Mounting	19" rack
Application	indoor
Power consumption	250W
Temperature range (operation)	0°C ~ +45°C
Blower	yes
Weight	4.2kg

EPS-1016

Available Accessories

Bild	Art. Nr. / Bezeichnung	Beschreibung
	211978 / EFC-S1310SFP	SFP Modul, Gigabit,10km, Singelmode 1310nm, Duplex LC Connector

Your Contact Person



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Deutschland
Tel.: +49 6074-888-333
E-Mail: info@eneo-security.com
Web: www.eneo-security.com