



2 Megapixel Full HD extreme backlight TVI vandalproof dome , IR LEDS

- 2 Megapixels CMOS, Colour/B&W Camera
- Varifocal Lens: f = 2.8 - 12 mm
- 0 Lux: Integrated LED IR Illuminator to see even in total darkness
- Weatherproof Outdoor Installation (IP66)
- Vandal Resistant Dome (IK10)
- 3 Axis Gimbal, to mount on Wall or Ceiling



ACCESSORIES

GBR-WA09

GBR-WA09J

GBR-CE04

GBR-CM04



GBR-PM04



Image Sensor:	1/2.7" progressive scan CMOS
Pixels - Effective:	1984(H) x 1105(V)
Scanning System:	PAL / NTSC
CoI/B:	Auto, IR-cut filter removable (ICR)
Sensitivity Colour:	0.014 lux @ F1.4 (AGC ON)
Sensitivity B/W:	0 Lux LED IR on
Lens Focal Length:	2.8 ~ 12 mm
Viewing Angle:	105.2° (H) ~ 32.8° (V)
S/N Ratio:	62 dB
Max. IR Distance:	Up to 40m
High Speed Shutter:	1/25 ~ 1/50.000 sec
Frame Rate:	25 fps (1920 x 1080)
White Balance:	3000K, 4200K, 6000K, 8000K, Auto, Push, User
BLC Back Light:	On/Off
Digital Noise Reduction (DNR):	On/Off
Reverse:	Mirror
Privacy Masking:	8 Zones
Motion Detection:	On/Off (4 Zones)
Video Outputs:	1x HD-TVI (BNC)
Coaxial control:	Control over Coax (CoC)
Protection Rating:	IK10, IP66
Operating Temperature:	-40°C ~ +60°C
Humidity:	less than 90%, non condensing
Supply Voltage:	12 Vdc
Power Consumption (W):	3
Weight:	0.9 kg - 1.98 lbs
Dimensions:	146 x 125 mm - 5.75 x 4.92 In