




4 Megapixel Compact Dome with IR Leds WDR

- 4 Megapixel IP Camera with Full HD 1080P real time video
- H.264 & MJPEG compression modes
- Lens: f = 2.8 mm, 106°
- 0 Lux: Integrated LED IR Illuminator to see even in total darkness
- Weatherproof Outdoor Installation (IP67)
- Built in analytics function, motion detection, trip wire, intrusion detection, tamper detection



DIMENSIONS (mm)



ACCESSORIES

GBR-WA06



FOR A GOOD REASON

GRUNDIG

TECHNICAL SPECIFICATIONS

| | |
|--------------------------------|---|
| Image Sensor: | 1/3" Progressive Scan CMOS |
| Pixels - Total: | 2688(H) x 1520 (V) |
| Sensitivity Colour: | 0.01 lux @ F1.2 (AGC ON) |
| Sensitivity B/W: | 0 Lux LED IR on |
| Co/B: | Auto/Timing/B&W/Color |
| Lens Focal Length: | 2.8 mm |
| Horizontal Viewing Angle: | 106° |
| Iris F-Number: | F 2.0 |
| High Speed Shutter: | 1/3 ~ 1/10.000 sec |
| IR LED: | 10 pcs. |
| Max. IR Distance: | 10 m |
| Wavelength: | 850nm |
| BLC Back Light: | On/ Off/ Area/ Level |
| WDR: | 120dB |
| Digital Noise Reduction (DNR): | 3D-DNR, auto |
| Reverse: | Normal, Flip, Mirror, Vertical Mode, 180° |
| Video Text Overlay: | Text string (28 character), Subtitle (1 lines @ 44 character) |
| Privacy zones: | 4 zones, rectangle |
| Video Compression: | H.264, H.264+, MJPEG |
| Video Streaming: | Dual stream: H.264 + H.264 or H.264 + MJPEG |
| Video Resolution: | Main: 2688x1520 (20/20fps), 2048x1536 (20/20fps), 1920x1080 (25/30fps), 1280x720 (25/30fps), Sub: 1280x720(25/30fps), 640x480(25/30fps), 352x288(25/30fps), 320x240(25/30fps) |
| Bit Rate: | Mainstream: 32kbps~16384kbps, Substream: 32kbps~8192Mbps |
| Alarm Trigger: | Motion detection, Video Tampering, Alarm Input, Network disconnect, IP address conflict, Storage exception, Line crossing Detection, Intrusion detection |
| Network Protocol: | Bonjour, DDNS, DHCP, DNS, FTP, HTTP, HTTPS, IEEE 802.1 X, IGMP, IPv4/IPv6, NTP, PPPoE, QoS, RTCP, RTP, RTSP, SMTP, SNMP, TCP/IP, UDP, UPnP |
| System Compatibility: | CGI, ONVIF, PSIA |
| ONVIF compliant: | Profile S, Profile G |
| Web Browser: | MS Internet Explorer 7.0 (or higher) |
| Security: | HTTPS, IP FILTER, IEEE802.1x, Admin/User account |
| SD memory: | supports up to 128 GB capacity of micro SD/SDHC/SDXC memory |
| Network Interface: | 1x 10/100 Base T/TX (RJ-45) |
| Protection Rating: | IP67, IK08 |
| Operating Temperature: | -30°C ~ +60°C |
| Humidity: | less than 90%, non condensing |
| Supply Voltage: | 12 Vdc, PoE (IEEE 802.3af) |
| Power Consumption (W): | 5 |
| Weight: | 0.6 kg - 1.32 lbs |
| Dimensions: | 120 x 55 mm - 4.72 x 2.17 In |