



## VMC-5.6/2S-LCD

Article number: 90569

5.6" (14,3cm) LCD/TFT Service Monitor, LED, 640x480, 2x Composite, 2x Audio, 12VDC

### Mainfeatures

Colour service monitor

PAL/NTSC auto selection

2 Video and Audio inputs / Audio output

Supply voltage: 12 to 30VDC

Vibration immunity

Screen size: 5.6" (14.3cm)

Resolution of 640x480 px.

On-screen menu control

1.8 Ah battery pack with charger

Rugged carrying case

### Specifications

Resolution	640x480 (4:3)
Synchronization	internal
<b>Display:</b>	
Video standard	PAL / NTSC (auto selection)
Contrast ratio typical	500:1
Response time typical	25 ms
Brightness typical	200 cd/m <sup>2</sup>
Viewing angle vertical	120 °
Viewing angle horizontal	140 °
Screen size	5.6"
Screen Size (cm)	14,3 cm
<b>Features:</b>	
OSD function control	contrast, brightness, colour intensity, colour, sharpness, volume

# VMC-5.6/2S-LCD

## Continued Specifications

Menu languages	English
<b>Interfaces / Inputs / Outputs:</b>	
Video inputs	2x 1Vp-p, (C)VBS, 75ohms, Cinch adapter cable
Video inputs (type)	composite (CVBS)
Audio inputs	30mVss ~ 100mVss, 2
Audio output	0.5W / 8ohms
Serial interfaces	no
<b>General:</b>	
Dimensions (HxWxD)	68x240x156mm (including carrying case)
Colour	Anthracite-colored carrying case
Housing material	plastic
Housing color	black
Weight	1.1kg
Loudspeaker	built-in
Power consumption	4.6W
Supply voltage	12 ~ 24VDC
Temperature range (operation)	0°C ~ +50°C
<b>Scope of delivery:</b>	

## Your Contact Person



eneo is a registered trademark of  
 VIDEOR E. Hartig GmbH  
 Carl-Zeiss-Straße 8  
 63322 Rödermark  
 Deutschland  
 Tel.: +49 6074-888-333  
 E-Mail: info@eneo-security.com  
 Web: www.eneo-security.com