



## IAR-7SG1008MMA

Article number: 216473

Gigabit Switch, Managed, 135W, 8x PoE, 2x SFP, 2xRJ45, 10/100/1000 Mbps, 19", 1 U

### Mainfeatures

PoE Switch, Rack Montage

8x 10/100/1000 PoE Ports, IEEE 802.3af/at

ESD protection IEC61000-4-5 standard

Web configuration, Web management

Port mirroring, password, PoE Status LED Display

Temperature range -10°C ~ +50°C

Gigabit Uplink Ports: 2x RJ45, 2x SFP

Up to 30W per port, Total ≤135W

Managed L2 switch, Built in low-noise fans

VLAN, PoE management, MAC address table

CCTV mode allows transmission up to 250m @ 10Mbps

Rack mounting brackets included

### Specifications

Multicast compliant	yes
<b>Features:</b>	
Port mirror	yes
QoS	yes
SNMP	yes
<b>Network:</b>	
Internal switching capacity (Mpps)	17,9Mpps
Internal switching capacity (Gbit/s)	24Gbps
VLAN	yes
<b>Interfaces / Inputs / Outputs:</b>	
Ethernet interface	10Base-T, 100Base-TX, 1000Base-T
Ports	8x 10/100/1000Base-T, 2x 1000Base-T SFP, 2x 10/100/1000Base-TX

# IAR-7SG1008MMA

## Continued Specifications

Optical connection	SFP Port
<b>General:</b>	
Dimensions (HxWxD)	44,5x442x194,5mm
Number PoE ports	8
Switch type	Layer2 switch
Weight	1,5 kg
Blower	yes
Management	yes
Mounting	19" rack
PoE Power	135 W
Power over Ethernet	IEEE 802.3at
Supply voltage	100~240VAC
Temperature range (operation)	-10°C ~ +45°C
<b>Scope of delivery:</b>	
Parts supplied	manual, Mounting Bracket, power cord
<b>Notes:</b>	
Support standards	IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX, IEEE 802.ab 1000BaseT, IEEE 802.3z 1000BaseSX/LX, IEEE 802.3x Flow Control, IEEE 802.3at Power Over Ethernet (PoE+), IEEE 802.3af Power Over Ethernet (PoE), IEEE 802.1Q VLAN, IEEE 802.1D Spanning Tree Protocol, IEEE 802.1p Class of Service, IEEE 802.1X, IEC61000-4-2, IEC61000-4-5

# IAR-7SG1008MMA

## Available Accessories

Image	Prod. No / Label	Description
	211978 / EFC-S1310SFP	SFP Modul, Gigabit, 10km, Singelmode 1310nm, Duplex LC Connector
	216477 / SFP-1310S40	SFP Modul, 1.25Gbps, 20km, Singlemode, 1310nm, Duplex LC Connector -40°~+75°C
	216478 / SFP-1310M40	SFP Modul, 1.25Gbps, 550m, Multimode, 1310nm, Duplex LC Connector, -40°~+75°C
	216479 / SFP-0850M10	SFP Modul, 1.25Gbps, 550m, Multimode, 850nm, Duplex LC Connector, 0°~+70°C
	216566 / SFP-1310S10	SFP Modul, 1.25Gbps, 20km, Singlemode, 1310nm, Duplex LC Connector, 0°~+70°C
	216567 / SFP-0850MM10	SFP Modul, 155Mbps, 2km, Multimode, 850nm, Duplex LC Connector, 0°~+70°C

## Your Contact Person



eneo is a registered trademark of  
 VIDEOR E. Hartig GmbH  
 Carl-Zeiss-Straße 8  
 63322 Rödermark  
 Deutschland  
 Tel.: +49 6074-888-333  
 E-Mail: info@eneo-security.com  
 Web: www.eneo-security.com