



MPD-62V2812P0B

Article number: 219546

1/2,8" HD Dome, Fix, Day&Night 1920x1080, Infrared, 2,8-12mm, WDR, 12VDC, Indoor

| | |
|---|--|
| 1/2,8" 2.3 Megapixel progressive scan CMOS sensor | Removable infrared cut filter |
| Compact plastic housing for indoor use | 3D-DNR noise reduction |
| Resolution max. 1920x1080 (Full HD) | Digital Wide Dynamic Range (D-WDR) |
| Multisignal: HD-TVI, AHD, CVI, Composite selectable | Integral motion detection |
| Variofocal 2.8-12mm day&night lens | Wedge adapter included (10° inclination) |
| LSC (Lens shading compensation) | Scratch resistant hard coated bubble |

Specifications

| Camera: | | Features: | |
|------------------------------------|--|--------------------------------|--|
| Camera type | Dome | Vertical tilt range | 65 °(25 - 90°) |
| Sensor size | 1/2,8" | OSD function control | OSD camera setup |
| Resolution pixels | 1920x1080, 960x576 | Menu languages | German, English, French, Italian, Spanish, Turkish, Dutch, Portugese, Polish, Chinese, Russian |
| Imager | CMOS, Sony, Sensor IMX322 | Privacy zones masking | Areas-ON/OFF switchable |
| System | True Day&Night | Mirror function | rotation, mirror, V flip |
| Sensitivity | 0,3 Lux, at F1.3, 40IRE | Digital Noise Reduction (DNR) | yes |
| Low speed shutter | yes, 2x ~ 30x | Interfaces / Inputs / Outputs: | |
| Manual electronic shutter (MES) | 1/25 ~ 1/50.000sec. | Video outputs | HD-TVI, AHD, CVI, composite (CVBS) |
| Automatic electronic shutter (ESC) | 1/25 ~ 1/50.000sec.. | External connections | video (BNC), 12VDC power input, connection cable approx.15cm |
| Wide Dynamic Range (WDR) | D-WDR | Alarm inputs | no |
| Flickerless function | yes | Alarm outputs | no |
| Backlight compensation | BLC, HLC | Serial interfaces protocols | UTC |
| IR cut filter | switchable | General: | |
| White balance | ATW, AWB, manual, outdoor, indoor, AWC | Dimensions (HxWxD) | 100x116mm |
| Signal-to-noise ratio | 52db | Illumination | infrared, 2x High Power LEDs 850nm |
| | | Illumination range | approx. 30m |
| | | Colour (housing) | white |
| | | Colour (bubble) | clear |
| | | Housing | indoor |
| | | Housing material | plastic |
| | | Weight | 260g |
| | | Heater | no |
| | | Power consumption | 6W |
| | | Mounting | wall mount, ceiling mount |
| | | Supply voltage | 12VDC |
| | | Temperature range (operation) | -10°C ~ +50°C |
| | | Text display | supplied |
| | | Vandalism resistant | no |
| | | Scope of delivery: | |
| | | Parts supplied | manual, screw set, Video sub-out cable, drilling template, bag of screws |
| Video: | | | |
| Video standard | PAL/NTSC | | |
| Signal format | Composite (FBAS), HD-TVI @ 2MP, AHD @ 2MP, CVI @ 2MP | | |
| Frame rate | 25/30fps @ 1920x1080p | | |
| Synchronization | internal | | |
| Lens: | | | |
| Lens type | varifocal | | |
| Zoom factor | 4x | | |
| Focal length | 2,8 - 12 mm | | |
| Digital zoom | no | | |
| MOD (Minimum object distance) | 0,5 m | | |
| Aperture range (F) | F1,3 | | |
| Iris control | DC | | |
| Vertical angle of view | 53 - 17 ° | | |
| Horizontal angle of view | 98 - 31 ° | | |
| Features: | | | |
| Motion detector | yes | | |

Related Products



PS12DC-11 | SKU: 218653

More product information

Exact focus setting aid

Hard Coated Bubble (Hardness grade - H) -- Anti Scratch Protection

Product recommendations



TVA-1201TRA|SKU: 212984



TVA-1201TRP|SKU: 212985



MAM-5ME1001MTA|SKU: 217344



MAM-5MM1001M0A|SKU: 220299



MAM-6ME1012MTA|SKU: 219643

