



IPC-52A0003M0B

Article number: 219027

1/2,8" Network Camera, 1920x1080, Day&Night, AF Zoom, WDR, 3,2-9 mm, Indoor

1/2,8" Sony STARVIS CMOS

Resolution max. 1920x1080 (Full HD)

Optical 3x Auto Focus Zoom, 16x Digital

3-9 mm day&night zoom lens, IR cut filter

VerticalView 90°/270° mode only H.264, HTML5 Playback

DOL-WDR by triple scan images at 30/25fps

VCA Video Analytic, ONVIF Event Mapping

Cross Web Browsing (IE, Safari, Firefox, Chrome)

Responsive Web Design, Zero configuration

Triple Streaming: 2x H.264, 1x MJPEG

Slot for Micro SD card

ONVIF conformity, PoE IEEE802.af

Specifications

Camera:		Features:	
Camera type	Zoom Camera	e-PTZ support	yes
Sensor size	1/2.8"	Internal storage	microSDHC card, microSDXC card
Resolution standard	HD 1080p	Menu languages	English, German, French, Polish, Finnish
Imager	CMOS, Sony STARVIS, Sensor IMX290	Privacy zones masking	Areas-ON/OFF switchable
System	True Day&Night	Remote configuration	web browser
Sensitivity	0,1 Lux, at F1.6, 40IRE	Web browser	MS internet Explorer: ActiveX ex 9.0, Safari: MJPEG, Mozilla: MJPEG, Google Chrome: MJPEG, Edge: MJPEG
Low speed shutter	yes, automatic	User interface	Type A (orange / grey)
Manual electronic shutter (MES)	1/25-1/60000sec.	Mirror function	mirror, flip
Automatic electronic shutter (ESC)	1/25 ~ 1/60.000sec.	Digital Noise Reduction (DNR)	yes
Wide Dynamic Range (WDR)	DOL-WDR 120dB	Network:	
Flickerless function	yes	Network protocols	TCP/IP, UDP, IPv4, IPv6, HTTP, HTTPS, FTP, UPnP, RTP, RTSP, RTCP, DHCP, ARP, Zeroconf, Bonjour
Backlight compensation	BLC, HLC	Interfaces / Inputs / Outputs:	
Day/Night switching	extern (Sensor), day, night, auto, night-color mode	Video outputs	composite (CVBS)
IR cut filter	switchable	External connections	RJ-45, audio input/output, alarm in/output, voltage input, micro SD card slot
White balance	automatic, ATW, manual	Ethernet interface	10Base-T, 100Base-TX
Signal-to-noise ratio	50dB	Alarm inputs	1
		Alarm outputs	1
		Serial interfaces	Ethernet
		General:	
		Series	KN-Series, eneo Candid Box
		Dimensions (HxWxD)	72x74x125mm
		Mount	1/4" UNC, 2x M6
		Illumination	no
		Colour (housing)	Pantone Cool Gray 1C
		Housing	indoor
		Housing material	aluminium
		Weight	450g
		Power consumption	6.5W
		Blower	no
		ONVIF	ONVIF Profile S
		Power over Ethernet	IEEE 802.3af
		SDK	upon request
		Supply voltage	12VDC, 24VAC, PoE
		Temperature range (operation)	-10°C ~ +50°C
		Text display	supplied
		Scope of delivery:	
		Parts supplied	manual, eneo Site Manager
Video:			
Resolution	1920x1080 (16:9), 1600x900 (16:9), 1280x720 (16:9), 960x540 (16:9), 640x360 (16:9), 320x180 (16:9)		
Resolution max.	1920x1080		
Stream types	2x H.264, 1x MJPEG multiple		
Image transmission rate max.	30 fps		
Multicast compliant	yes		
Compression standard	H.264, M-JPEG		
Lens:			
Lens type	auto focus zoom		
Zoom factor	2,8x		
Focal length	3,2 - 9 mm		
Digital zoom	12x		
MOD (Minimum object distance)	0,5 m		
Iris control	DC		
Vertical angle of view	53 - 4 °		
Horizontal angle of view	102 - 8 °		
Features:			
Motion detector	yes		
Analysis functions	motion detection, tampering protection, trip wire detection with counting and direction detection, Field detection, Defog		
Alarm processing	recording internal storage, E-Mail, HTTP, FTP, Boost, TCP, UDP, Onvif Event Mapping, alarm out		
Audio	2 Way Audio		
Audio support	yes		
Password protection	yes		

Related Products



VHM/ECLKB-W|SKU: 79676



PS12DC-11|SKU: 218653



WD-30|SKU: 219504

More product information

Preset Zoom (4 adjustable positions)

Product recommendations



IAR-7SE1024MMA|SKU: 214460



IAM-5SE1008MUA|SKU: 214459



IAM-5SG1008MMA|SKU: 216129



IAD-5SG1004MUA|SKU: 216469



IAD-5SG1008MUA|SKU: 216472



IAR-7SG1008MMA|SKU: 216473



IAR-7SG1016MMA|SKU: 216474



IAR-7SG1024MMA|SKU: 216682



eneo Site Manager|SKU: 218218

