



VM-HD19P

Article number: 224195

19" (48cm) LCD Monitor HD 1280x1024, LED, HDMI, VGA, Composite

| Professional 19" (48 cm) LCD monitor | Perfect presentation through digital 3D filtering and noise reduction |
|--|---|
| Industrial design built to run 24x7x365 continuously | |
| | Different video inputs HDMI, VGA, Composite |
| Maximum resolution 1280x1024 pixels | Built-in speakers |
| LED Back Light | Supply Voltage: 12VDC |
| Fast response time 5ms | Plastic cabinet including stand |

Specifications

| Display: | |
|--------------------------|-----------------------|
| Resolution pixels | 1280x1024 |
| Video standard | PAL/NTSC |
| Resolution | 1280x1024 (5:4) |
| Aspect ratio | 5:4 |
| Contrast ratio typical | 1000:1 |
| Response time typical | 5 ms |
| Brightness typical | 300 cd/m ² |
| Backlighting | LED |
| Viewing angle vertical | 178° |
| Viewing angle horizontal | 178 ° |
| Screen size | 19" |
| Screen Size (cm) | 48 cm |

| Features: | |
|----------------|----------------------------------|
| Comb filter | 3D comb filter with de-interlace |
| Menu languages | English |

| Interfaces / Inputs / Outputs: | |
|--------------------------------|--------------------------------|
| Video inputs (type) | VGA, HDMI, 2x composite (CVBS) |
| Audio inputs | 1x 3.5mm jack, 1 |
| Audio output | 1x 3,5mm jack |
| Serial interfaces | no |

| General: | |
|-------------------------------|-----------------------|
| Dimensions (HxWxD) | 408,9x425,1x44,8mm |
| Mount | VESA standard 75x75mm |
| Housing material | plastic |
| Housing color | black |
| Weight | 3kg |
| Loudspeaker | 2 |
| Power consumption | 26.5W |
| Supply voltage | 12VDC |
| Temperature range (operation) | -30°C ~ +85°C |

| Scope of delivery: | |
|--------------------|---|
| Parts supplied | manual, power cord, PSU 100~240VAC, IR remote |
| | controller, VGA cable, feet |

Related Products