



IAM-5SE1004MUD

Article number: 228224

Switch, Unmanaged, 120W, 4xPoE 1x RJ45, 1x SFP 100Mbps, Industrial Design, -40°C~+75°C

Ethernet PoE Switch, DIN Rail

Uplink ports 1xRJ45, 1xSFP

4x 10/100 PoE Ports, IEEE 802.3af/at

Up to 30W per port

Surge protection IEC61000-4-5 (6KV)

Status LED: Uplink, PoE, Optical port, Power

CCTV mode allows transmission up to 250m @ 10Mbps

Temperature range -40° C ~ +75° C

Specifications

Features:	
Multicast compliant	no
Port mirror	no
QoS	no
SNMP	no
Network:	
Ethernet Standards	IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX, IEEE 802.3at Power Over Ethernet (PoE+), IEEE 802.3af Power Over Ethernet (PoE)
Internal switching capacity (Mpps)	0,9 Mpps
Internal switching capacity (Gbit/s)	1,5 Gbps
VLAN	yes
Interfaces / Inputs / Outputs:	
Ethernet interface	10Base-T, 100Base-TX
Ports	4x 10/100Base-TX, 1x 100 SFP, 1x 10/100Base-TX
Optical connection	SFP Port
General:	
Dimensions (HxWxD)	46x110x159mm
Number PoE ports	4
Model	DIN rail module
Type	Layer2 switch
Weight	530g
Blower	no
Management	no
Mounting	DIN rail, wall mount
PoE Power	120 W
Power over Ethernet	IEEE 802.3at
Supply voltage	48-57 VDC
Temperature range (operation)	-40°C ~ +75°C
Scope of delivery:	
Parts supplied	manual, power cord, Mounting Bracket, PSU
Notes:	
Application	indoor
Trunk	Contact discharge 6KV, Air discharge 8KV, IEC61000-4-2, IEC61000-4-5

Product recommendations



SFP-0850MM10|SKU: 216567

