

GD-ML-BC2230HD

54.6 cm (21.5") LCD/TFT Monitor LED 16:9



- Displays a full, flat 21,5" (54.6 cm) diagonal image
- Designed for professional 24/7 usage
- LED Backpanel illumination
- Built-in Speaker
- 1 HDMI, 1 VGA Input



ESSENTIAL

- Product Line Essential: high quality, basic features and remarkably many functions for smaller applications

Specifications GD-ML-BC2230HD

Monitor

LCD Panel size:	54.6 cm (21, 5") Diagonal AM-TFT LED Backlight
Pixels - Total:	1920 (H) x 1080 (V)
Pixel Pitch:	0.248 mm (H) x 0.248 mm (V)
Aspect Ratio:	16 : 9
Viewing Angle:	178° (H) ~ 178° (V)

Video

Video Inputs:	1x HDMI, 1x VGA
Video Standard:	PAL, NTSC
Brightness:	250 cd, m ²
Contrast Ratio:	1000:1
Number of Colours:	16.7 million
Response Time:	5 ms

General

Speakers:	2 x 2 W
OSD (On Screen Display):	Yes, multi language
Accessories included:	Power Adapter and HDMI cable

Approvals

Regulation:	CE, EAC, FCC, RoHS Compliant
MTBF at 25° C:	> 100,000 hours

Environmental

Operating Temperature:	0 °C ~ +40 °C
Humidity:	less than 90%, non condensing

Electrical

Supply Voltage:	12 VDC, Power Adapter 100 ~ 240 VAC 50, 60Hz included
Power Consumption:	20 W

Mechanical

Vesa Mount:	100 x 100 mm
Dimensions:	491 x 298 x 137 mm
Weight:	3500 g (7,72 lb)

Dimensions:

