

# IAM-5SE1008MUB

SKU: 228223



Gigabit Switch, 8xPoE 100Mbps, 1x RJ45, 1x SFP  
1000Mbps, Unmanaged, Industrial Design

## Main Features

Gigabit PoE switch, DIN Rail

Gigabit Uplink ports 1xRJ45, 1xSFP

8x 10/100 PoE Ports, IEEE 802.3af/at

Up to 30W per port

Surge protection IEC61000-4-5 (6KV)

Status LED: Uplink, PoE, Optical port, Power

PoE reset button for each port

CCTV mode allows transmission up to 250m @ 10Mbps

Temperature range -40° C ~ +75° C

## Specifications

Functions:	
Multicast compliant	no
Port mirror	no
QoS	no
SNMP	no
Network:	
Ethernet standards	IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX, IEEE 802.3ab 1000BaseT, IEEE 802.3z 1000BaseSX/LX, IEEE 802.3at Power Over Ethernet (PoE+), IEEE 802.3af Power Over Ethernet (PoE)
Internal switching capacity (Mpps)	4,2 Mpps
Internal switching capacity (Gbit/s)	5,6 Gbps
VLAN	yes

# IAM-5SE1008MUB

## Continuation of the specifications

Interfaces / Inputs/ Outputs:	
Ethernet interface	10Base-T,100Base-TX,1000Base-T
Ports	8x 10/100Base-TX,1x 10/100/1000T SFP,1x 10/100/1000Base-Tx
Optical connector	SFP Port
General:	
Dimensions (HxWxD)	46,5x110x159mm
Weight	530g
PoE ports (number)	8
Model	DIN rail module
Type	Unmanaged
Blower	no
Management	no
Mounting	DIN rail,wall mount
PoE budget	120 W
Power over Ethernet	IEEE 802.3af,IEEE 802.3at
Supply voltage	48~57 VDC
Operating temperature	-40°C ~ +75°C
Application	indoor
Trunk	Contact discharge 6KV,Air discharge 8KV,IEC61000-4-2,IEC61000-4-5
Parts supplied:	
Parts supplied	manual,power cord,Mounting Bracket,PSU

## Optional Accessory

SKU	Name	Description
214832	DRP-240-48	Power Supply IAM-5 Series 240W, DIN Rail
219525	RJT-1000SFP	RJ45- SFP Transceiver Modul, 1000Base-T, 0°~+70°C
216479	SFP-0850M10	SFP Modul, 1,25Gbps, 550m, Multimode, 850nm, Duplex LC Connector, 0°~+70°C
218758	SFP-0850M40	SFP Modul, 1,25Gbps, 550m, Multimode, 850nm, Duplex LC Connector, -40° ~ +70°C
216478	SFP-1310M40	SFP Modul, 1,25Gbps, 550m, Multimode, 1310nm, Duplex LC Connector, -40°~+75°C
216566	SFP-1310S10	SFP Modul, 1,25Gbps, 20km, Singlemode, 1310nm, Duplex LC Connector, 0°~+70°C
216477	SFP-1310S40	SFP Modul, 1,25Gbps, 20km, Singlemode, 1310nm, Duplex LC Connector -40°~+75°C



eneo is a registered trademark of  
VIDEOR E. Hartig GmbH  
Carl-Zeiss-Straße 8  
63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300  
Fax: +49 6074 - 888 - 100  
E-Mail: info@eneo-security.com  
Web: www.eneo-security.com

Stay informed and subscribe  
to the eneo newsletter

