

IAM-5SE1004IUP

SKU: 237908



Gigabit Switch, Unmanaged 90W, 4x PoE, Industrie Design, -20°C~+65°C, PD Port

Main Features

- Gigabit PoE Switch, DIN Rail
- 4x 10/100/1000 PoE Ports, IEEE 802.3af/at/bt
- Maximal 90W Power Budget
- 1 x SFP Gigabit Uplink Port
- 1 x RJ45 Gigabit Uplink Port, PD-fähig (90W PoE Input)

- CCTV-Mode, erweiterte Übertragungsdistanz
- 1 x Ausgangsrelais
- Überspannungsschutz IEC61000-4-5 (6KV)
- Temperaturbereich -20°C ~ +65°C

Specifications

Other	
Dimensions (HxWxD)	44x110x160mm
Type	Unmanaged
Series	eneo Switch
Mounting	DIN rail
Blower	no
Ethernet interface	1000Base-T, 100Base-TX, 10Base-T
VLAN	no
Ports	1x 10/100/1000Base-T (PoE-PD), 1x 1000Base-X SFP, 4x 10/100/1000Base-T
PoE ports (number)	4
Management	no
Model	DIN rail module

IAM-5SE1004IUP

Continuation of the specifications

Supply voltage	48~57 VDC, PoE
Power consumption	130W
Power over Ethernet	IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt
PoE budget	120 W
Operating temperature	-40°C ~ +65°C
Weight	540g
Manufacturer order number	237908

Optional Accessory

SKU	Name	Description
216568	NE-60PoE	PoE Injector, 60W, for Switch IAD-5SG1004MUA and IAM-5SE1004MUP
219525	RJT-1000SFP	RJ45- SFP Transceiver Modul, 1000Base-T, 0°~+70°C
216479	SFP-0850M10	SFP Modul, 1.25Gbps, 550m, Multimode, 850nm, Duplex LC Connector, 0°~+70°C
218758	SFP-0850M40	SFP Modul, 1.25Gbps, 550m, Multimode, 850nm, Duplex LC Connector, -40° ~ +70°C
216478	SFP-1310M40	SFP Modul, 1.25Gbps, 550m, Multimode, 1310nm, Duplex LC Connector, -40°~+75°C
216566	SFP-1310S10	SFP Modul, 1.25Gbps, 20km, Singlemode, 1310nm, Duplex LC Connector, 0°~+70°C
216477	SFP-1310S40	SFP Modul, 1.25Gbps, 20km, Singlemode, 1310nm, Duplex LC Connector -40°~+75°C



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8

63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300
Fax: +49 6074 - 888 - 100
E-Mail: info@eneo-security.com
Web: www.eneo-security.com

Stay informed and subscribe
to the eneo newsletter

