

IND-58F0002MTPA

SKU: 238644



Network Camera Turret, Panorama 180°, 2x Sensor, Lens 2.8mm, max. 3840x2160, AI, DWDR, IR, WL, PoE, 12VDC, IP67

Main Features

Multisensor 2x 1/2.7' CMOS sensor, panorama	Smart Codec H.265/H.264, dual streaming
Maximum resolution 5120x1440 pixels each, 15fps	Browser-independent (Edge, Safari, Firefox, Chrome)
Panorama ultra wide-angle camera 180° HFoV, 32:9	Supports ONVIF profiles S/T/G and audio
AI analysis functions including object classification	Local storage via micro SD card
WDR, BLC, HLC and 3D-DNR noise reduction	NDA compliance
Lenses with 2.8mm fixed focal length	Integrated IR and white light LED illumination, IP67

Specifications

General:	
EAN/GTIN	4260229840726
Dimensions (HxWxD)	112,4x135mm
Illumination	3xHigh power LEDs 850nm,2x Whitelight LED,Infrared,White light
SDK	upon request
Text display	ON/OFF switchable
Series	eneo IN-Series
Camera Type	Multisensor Camera
Housing	Outdoor
Color (housing)	Pantone P 179-1, RAL9003

IND-58F0002MTPA

Continuation of the specifications

Housing material	Metal
Heater	no
Blower	no
Mounting	Ceiling mount, Wall mount
Supply voltage	12VDC, PoE
Power consumption	max. 8,88W
Power over Ethernet	IEEE 802.3af
Vandal proof	no
Operating temperature	-30°C ~ +60°C, @ Humidity 90% or less (non-condensing)
ONVIF	ONVIF Profile G, ONVIF Profile M, ONVIF Profile S, ONVIF Profile T
Protection rating	IP67
Illumination range	approx. 30m, Warm light approx. 15m
Weight	765g
DORI:	
Observe (62 px/m)	40,1 m
Recognize (125 px/m)	21,7 m
Identify (250 px/m)	10,7 m
Detect (25px/m)	108,3 m
Functions:	
Alarm processing	recording internal storage (SD card), E-Mail, HTTP, FTP, TCP, UDP, Red & blue flashing lights, Siren, Cloud Upload
Motion detector	yes
Menu languages	English, German, French, Italian, Portuguese, Spanish, Turkish, Russian, Japanese
Mirror function	108° flip
Multicast compliant	yes
Password protection	administrator & users
Privacy zone masking	Areas-ON/OFF switchable
Web browser	MS Internet Explorer 10/11, Safari, Firefox, Google Chrome, Edge
Digital Noise Reduction	3D-DNR, yes
Audio support	yes
Internal storage	microSD-Kartenslot
Analysis functions	Cross Counting (CC), Crowd Density Detection (CD), Face Recognition (FR), Heat Map (HM), Human&Vehicle Detection (PD&VD), License Plate Recognition (LPR), Line Crossing Detection (LCD), Perimeter Intrusion Detection (PID), Queue Length Detection (QD), Rare Sound Detection (RSD), Region Entrance, Region Exiting
Audio	2 Way Audio, built-in loudspeaker, built-in microphone

IND-58F0002MTPA

Continuation of the specifications

Remote configuration	Browser
Camera:	
Imager	Progressive scan, Sensor SC500AI, Chipset NT98529, CMOS
Automatic electronic shutter (ESC)	1/5 ~ 1/20.000sec.
Flickerless function	yes
Backlight compensation	BLC, HLC
Low speed shutter	yes
Manual electronic shutter (MES)	1/5 ~ 1/20.000sec.
Day&Night mode	Day, Night, Automatic, Time
White balance	Automatic, Manual
Wide Dynamic Range (WDR)	D-WDR
Resolution Standard	8 Megapixel
System	24h color, True Day&Night
Sensor size	1/2.7"
Day&Night switch	Electronic
Sensitivity	0,001 Lux at F1,6
Camera type	Dome
Parts supplied:	
Parts supplied	manual, bag of screws
Network:	
Network protocols	IPv4, IPv6, TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, SMTP, NTP, UPnP, SNMP, HTTPS, FTP, UDP, PPPoE
Lens:	
Lens Type	fixed focal length
Focal Length	2,8 mm
Iris Control	DC
Digital Zoom	yes
MOD (Minimum Object Distance)	2 m
Interfaces / Inputs/ Outputs:	
External connectors	RJ-45, 12VDC input (DC plug), connection cable approx. 30cm, micro SD card slot 256 GB
Video outputs	no
Alarm inputs	nein
Alarm outputs	no
Ethernet interface	100Base-TX, 10Base-T
Serial interfaces	Ethernet
Video:	
Resolution	5120x1440, 4608x1296, 4096x1152, 3840x1080, 3072x864, 1536x432, 1024x288
Image display	32:9
Stream types	Dual Streaming

IND-58F0002MTPA

Continuation of the specifications

Video compression	H.264, H.264+ (Smart Stream), H.265, H.265+ (Smart Stream), M-JPEG
Image resolution max.	5120x1440
Image Transmission Rate	15 fps
Other	
Remarks	To guarantee you an optimum user experience, we recommend that you only use components of the same brand in a system. If several brands are used in combination, eneo cannot guarantee functionality. If combined use is necessary, we offer a compatibility check for a fee (for more information, see article number #229235 at VIDEOR).,NDAA compliance under Section 889
Horizontal Angle of View	180°
Manufacturer order number	238644

Optional Accessory

SKU	Name	Description
236198	eneo INsight Installation Tool	Supports adjustments for cameras with AI features for IN-series
218218	eneo Site Manager	Management Software for eneo IP products
239837	KBD-3NET	Network keyboard with joystick, supports ONVIF protocol, RJ45, 12VDC



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8

63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300
Fax: +49 6074 - 888 - 100
E-Mail: info@eneo-security.com
Web: www.eneo-security.com

Stay informed and subscribe
to the eneo newsletter

