

NSUI-3004M0A

242369



Gigabit Switch Industrial, Unmanaged, 4x PoE, 1xRJ45, 1xSFP, 30W each Port, -40°C~75°C, 44~57 VDC

Main Features

5 RJ45 ports with 10/100/1000 Mbps	High EMC protection level
1 Gigabit SFP port for fiber optic uplink	Plug-and-play, no configuration, easy to use
4 PoE+ ports, each with up to 30W power	Redundant power supply 44-57VDC
Total PoE power: up to 60 watts	Robust IP30 housing, DIN-RAIL or wall mounting
Supports IEEE 802.3af/at standards	Operating temperature range: -40-75°C
Silent operation thanks to fanless design	Power supply not included

Specifications

Other	
Dimensions (HxWxD)	38,5x136x108mm
Construction	DIN rail module
Remarks	Power supply unit is not included in the scope of delivery,To achieve the specified PoE budget (total) value, please use suitable power supplies or PoE injector.PoE budget: 90W max. for a single PoE port; 75W max. for all PoE ports when supplied via PD port; 120 W max. for all PoE ports when supplied via DC input
Special features	Die empfohlene Standardleistung ist von der Leistung der externen Netzteile in Industriequalität abhängig. Dieses Produkt hat 4 POE-Ports. Im Hinblick auf die Verträglichkeit mit einem 60W-Netzteil beträgt die POE-Leistung etwa 55W. Sind 4 Anschlüsse mit einem 120-W-Industrienetzteil eingerichtet, kann eine Leistung von bis zu 115 W bereitgestellt werden.

NSUI-3004M0A

Trunk	IEC61000-4-2,IEC61000-4-5
Internal switching capacity (Gbit/s)	12 Gbps
Internal switching capacity (Mpps)	8,9 Mpps
Parts supplied	manual, 1x DIN Rail
Multicast compliant	no
Ethernet standards	IEEE 802.3 10BaseT,IEEE 802.3u 100BaseTX,IEEE 802.3x Flow Control,IEEE 802.3af Power Over Ethernet (PoE),IEEE 802.3at Power Over Ethernet (PoE+)
Optical connector	SFP Port
Port mirror	no
QoS	no
SNMP	no
Type	Unmanaged
Series	eneo Switch
Mounting	DIN rail, wall mount
Blower	no
Ethernet interface	1000Base-T, 100Base-TX, 10Base-T
VLAN	no
Ports	1x 1000Mbps SFP, 5x 10/100/1000Mbps
PoE ports (number)	4
Management	no
Supply voltage	44~57 VDC
Power consumption	65W
Power over Ethernet	IEEE 802.3af, IEEE 802.3at
PoE budget	60 W
Operating temperature	-40°C ~ +75°C, @ Humidity 10%-90% (non-condensing)
Weight	939g

NSUI-3004M0A

Optional Accessory


SKU	Name	Description
242377	NSFP-20000DLC	SFP Module, 1.25 Gbps, 20KM, Duplex LC, Tx/Rx at 1310 nm, hot-plug, SFP MSA-compliant, Digital Monitoring
242376	NSFP-20000SLC	SFP Modul Pair, 1.25 Gbps, 20 km, Simplex LC, Tx/Rx at 1310/1550nm, SFP MSA-compliant, Digital Monitoring
242375	NSFP-20000SSC	SFP Modul Pair, 1,25Gbps, 20KM, Simplex SC, Tx/Rx at 1310/1550nm, SFP MSA-compliant, Digital Monitoring
242374	NSFP-3000SLC	SFP Modul Pair, 1,25Gbps, 3KM, Simplex LC, Tx/Rx at 1310/1550nm, SFP MSA-compliant, Digital Monitoring
242373	NSFP-3000SSC	SFP Modul Pair, 1,25Gbps, 3KM, Simplex SC, Tx/Rx at 1310/1550nm, SFP MSA-compliant, Digital Monitoring



- NSFP-20000SSC
- NSFP-3000SSC



- NSFP-3000SLC
- NSFP-20000SLC



- NSFP-20000DLC



- DT-82 (48Vdc/2A)

