

NSUR-1024M0A

242365



Gigabit Switch Rack, Unmanaged, 24x PoE, 2xSFP, max. 30W each Port, integrated Power Supply max. 400W

Main Features

24 RJ45 ports with 10/100/1000 Mbps	8K MAC address table supported
2 Gigabit SFP ports for fiber uplink	Forwarding rate: up to 38.688 Mpps
24 PoE+ ports, up to 30W per port	Switching capacity: 52 Gbps backplane
Total PoE power budget: 400 Watts	Supports Energy Efficient Ethernet (802.3az)
Supports IEEE 802.3af/at/az standards	Rugged 19" metal case, 440×290×44 mm
Non-blocking wire-speed on all ports	Operating temperature: 0–45 °C

Specifications

Other	
Dimensions (HxWxD)	44,5x440x290mm
Construction	Desktop
Trunk	IEC61000-4-2,IEC61000-4-5
Internal switching capacity (Gbit/s)	52Gbps
Internal switching capacity (Mpps)	38,688Mpps
Parts supplied	manual,power cord,19" rack mount angle
Multicast compliant	no
Ethernet standards	IEEE 802.3 10BaseT,IEEE 802.3u 100BaseTX,IEEE 802.ab 1000BaseT,IEEE 802.3x Flow Control,IEEE 802.3at Power Over Ethernet (PoE+),IEEE 802.3af Power Over Ethernet (PoE)

NSUR-1024M0A

Optical connector	SFP Port
Port mirror	no
QoS	no
SNMP	no
Type	Unmanaged
Series	eneo Switch
Mounting	19" rack, desktop
Blower	no
Ethernet interface	1000Base-T, 100Base-TX, 10Base-T
VLAN	no
Ports	24x 10/100/1000Base-TX, 2x 1000Mbps SFP
PoE ports (number)	24
Management	no
Supply voltage	100-240VAC
Power over Ethernet	IEEE 802.3af, IEEE 802.3at
PoE budget	380 W
Operating temperature	0°C ~ +45°C, @ Humidity 10%-90% (non-condensing)
Weight	3.5kg
Manufacturer order number	242365

NSUR-1024M0A

Optional Accessory


SKU	Name	Description
242377	NSFP-20000DLC	SFP Module, 1.25 Gbps, 20KM, Duplex LC, Tx/Rx at 1310 nm, hot-plug, SFP MSA-compliant, Digital Monitoring
242376	NSFP-20000SLC	SFP Modul Pair, 1.25 Gbps, 20 km, Simplex LC, Tx/Rx at 1310/1550nm, SFP MSA-compliant, Digital Monitoring
242375	NSFP-20000SSC	SFP Modul Pair, 1,25Gbps, 20KM, Simplex SC, Tx/Rx at 1310/1550nm, SFP MSA-compliant, Digital Monitoring
242374	NSFP-3000SLC	SFP Modul Pair, 1,25Gbps, 3KM, Simplex LC, Tx/Rx at 1310/1550nm, SFP MSA-compliant, Digital Monitoring
242373	NSFP-3000SSC	SFP Modul Pair, 1,25Gbps, 3KM, Simplex SC, Tx/Rx at 1310/1550nm, SFP MSA-compliant, Digital Monitoring



- NSFP-20000SSC
- NSFP-3000SSC



- NSFP-3000SLC
- NSFP-20000SLC



- NSFP-20000DLC

