

NSMI-4008M0A

242372



Gigabit Switch Industrial, Managed, 8x PoE, 2xSFP, 30W each Port, -40°C~75°C, 44~57 VDC

Main Features

8 RJ45 ports with 10/100/1000 Mbps	Silent operation thanks to fanless design
2 Gigabit SFP ports for fiber optic uplink	High EMC protection level
8 PoE+ ports, each with up to 30W power	Supports VLAN, ACL, and ERPS ring network
Total PoE power: up to 240 watt, depending on the connection	Redundant power supply 44-57VDC
Supports IEEE 802.3af/at standards	Robust IP30 housing, DIN-RAIL or wall mounting
	Operating temperature range: -40-75°C

Specifications

Other	
Number of PoE ports	8
Design	DIN Rail Module
Dimensions (WxHxD) (extended)	50x149,2x122mm
Remark	Power supply unit is not included in the scope of delivery, To achieve the specified PoE budget (total) value, an appropriate optional power supply unit must be used.
ESD protection	IEC61000-4-2, IEC61000-4-5
Weight	1 kg
Scope of delivery	manual, 1x DIN Rail
Multicast	Yes

NSMI-4008M0A

Eneo _netzwerkstandards	IEEE 802.1D Spanning Tree Protocol, IEEE 802.1p QoS, IEEE 802.1p QoS, IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX, IEEE 802.3x Flow Control
QoS	DSCP Priority, QoS, QoS, QoS, QoS, WRR
Security	Fast Ring, Password, Port Isolation, Radius Authentication, Radius Authentication, Radius Authentication
Internal Switching Capacity (Gbit)	20 Gbps
Internal Switching Capacity (MP per second)	14.88 Mpps
Ethernet interface	1000Base-T, 100Base-TX, 10Base-T
Type	Smart Switch
Power consumption	10 W
Fan	No
Management	Yes
Mounting type	DIN Rail, Wall
Manufacturer order number	242372
PoE Budget (Total)	240 W
Power over Ethernet	IEEE 802.3af, IEEE 802.3at
Rack installation	No
Series	eneo Switch
Power supply	44-57VDC
Temperature Range (Operating)	-40°C ~ +75°C, @ Humidity 10%-90% (non-condensing)
VLAN	Yes

NSMI-4008M0A

Optional Accessory


SKU	Name	Description
242377	NSFP-20000DLC	SFP Module, 1.25 Gbps, 20KM, Duplex LC, Tx/Rx at 1310 nm, hot-plug, SFP MSA-compliant, Digital Monitoring
242376	NSFP-20000SLC	SFP Modul Pair, 1.25 Gbps, 20 km, Simplex LC, Tx/Rx at 1310/1550nm, SFP MSA-compliant, Digital Monitoring
242375	NSFP-20000SSC	SFP Modul Pair, 1,25Gbps, 20KM, Simplex SC, Tx/Rx at 1310/1550nm, SFP MSA-compliant, Digital Monitoring
242374	NSFP-3000SLC	SFP Modul Pair, 1,25Gbps, 3KM, Simplex LC, Tx/Rx at 1310/1550nm, SFP MSA-compliant, Digital Monitoring
242373	NSFP-3000SSC	SFP Modul Pair, 1,25Gbps, 3KM, Simplex SC, Tx/Rx at 1310/1550nm, SFP MSA-compliant, Digital Monitoring



- NSFP-20000SSC
- NSFP-3000SSC



- NSFP-3000SLC
- NSFP-20000SLC



- NSFP-20000DLC



- DT-82 (48Vdc/2A)

