

NSMR-2008M0A

242366



Gigabit Switch Rack, Managed, 8x PoE, 2xSFP, max. 30W each Port, internal Power Supply max. 150W

Main Features

8 RJ45 ports with 10/100/1000 Mbps	Supports MAC address auto-learning and auto-aging
2 Gigabit SFP ports for fiber optic uplink	Supports QoS, port mirroring, and link aggregation protocol
8 PoE+ ports, each with up to 30W power	PoE watchdog automatically detects and restarts PD devices
Total PoE power: up to 150 watts	Supports energy-efficient Ethernet (802.3az)
Supports IEEE 802.3af/at/az standards	Robust 19" metal housing, 271×182×45 mm
Silent operation thanks to fanless design	Operating temperature: 0-45°C

Specifications

Other	
Number of PoE ports	8
Design	Desktop
Dimensions (WxHxD) (extended)	44,5x271x181,5mm
ESD protection	IEC61000-4-2, IEC61000-4-5
Weight	1.35 kg
Scope of delivery	manual,power cord
Multicast	Yes
Eneo _netzwerkstandards	IEEE 802.1p QoS, IEEE 802.1p QoS, IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX, IEEE 802.3x Flow Control

NSMR-2008M0A

QoS	DSCP Priority, QoS, QoS, QoS, QoS, WRR
Security	Password, Port Isolation
Internal Switching Capacity (Gbit)	20 Gbps
Internal Switching Capacity (MP per second)	14.88 Mpps
Ethernet interface	1000Base-T, 100Base-TX, 10Base-T
Type	Smart Switch
Fan	No
Management	Yes
Mounting type	19" Rack Installation, Desktop
Manufacturer order number	242366
PoE Budget (Total)	150 W
Power over Ethernet	IEEE 802.3af, IEEE 802.3at
Rack installation	No
Series	eneo Switch
Temperature Range (Operating)	0°C ~ +45°C, @ Humidity 10%-90% (non-condensing)
VLAN	Yes

NSMR-2008M0A

Optional Accessory


SKU	Name	Description
242377	NSFP-20000DLC	SFP Module, 1.25 Gbps, 20KM, Duplex LC, Tx/Rx at 1310 nm, hot-plug, SFP MSA-compliant, Digital Monitoring
242376	NSFP-20000SLC	SFP Modul Pair, 1.25 Gbps, 20 km, Simplex LC, Tx/Rx at 1310/1550nm, SFP MSA-compliant, Digital Monitoring
242375	NSFP-20000SSC	SFP Modul Pair, 1,25Gbps, 20KM, Simplex SC, Tx/Rx at 1310/1550nm, SFP MSA-compliant, Digital Monitoring
242374	NSFP-3000SLC	SFP Modul Pair, 1,25Gbps, 3KM, Simplex LC, Tx/Rx at 1310/1550nm, SFP MSA-compliant, Digital Monitoring
242373	NSFP-3000SSC	SFP Modul Pair, 1,25Gbps, 3KM, Simplex SC, Tx/Rx at 1310/1550nm, SFP MSA-compliant, Digital Monitoring



- NSFP-20000SSC
- NSFP-3000SSC



- NSFP-3000SLC
- NSFP-20000SLC



- NSFP-20000DLC

