

NSFP-20000DLC

242377



SFP Module, 1.25 Gbps, 20KM, Duplex LC, Tx/Rx at 1310 nm, hot-plug, SFP MSA-compliant, Digital Monitoring

Main Features

1250 Mbps data rate on 9/125 µm SMF	Wide temp. range: -40°C to +85°C (industrial)
Dual-fiber design (separate TX and RX fibers)	Single 3.3V power supply
Up to 20 km range (single-mode fiber)	Metal housing for low EMI interference
LC optical connector	TX fault and Loss of Signal (LOS) alerts
Compliant with SFP MSA & SFF-8472	Low power consumption (< 300 mA)
Integrated Digital Diagnostics Monitoring (DDM)	RoHS compliant and lead-free

Specifications

Other	
Number of fibers	2
Design	Module
Mode	Single Mode
Dimensions (WxHxD) (extended)	14,2x12,5x56,3mm
Application environment	inside
Weight	17.05 g
Multicast	No
Transmission medium	Glass fibre
Type	SFP Module
Fiber Optic Connectors	Duplex LC

NSFP-20000DLC

Fan	No
Management	No
Manufacturer order number	242377
Rack installation	No
Reach	20 km
Temperature Range (Operating)	-40°C ~ +85°C
VLAN	No

