

MPC-52C0000M0B

243655



1/2.8" HD Camera, Day&Night, 1920x1080, WDR, C/CS, 12Vdc

Main Features

1/2.8" 2 Megapixel SONY STARVIS 2 CMOS sensor

Super low light performance by Sony STARVIS 2 technology

Resolution max. 1920x1080 pixels (Full HD)

Separate outputs for digital and multi-signal

Multisignal: HD-TVI, AHD, CVI and Composite selectable

Digital signal: EX-SDI, HD-SDI selectable

Removable infrared cut filter

ROI (Region of Interest) WDR mode

Integrated motion detector, defog, privacy zones

C/CS mount, LSC (Lens shading compensation)

Specifications

General	
Dimensions (WxHxD) (extended)	72x74x89mm
Text overlay	available
Housing type	Inside
Housing material	Aluminium
Power supply	12VDC
Temperature Range (Operating)	-10°C ~ +50°C, @ Luftfeuchtigkeit 20%-80% (nicht kondensierend)
Wide Dynamic Range (WDR)	D-WDR
Camera	
Recording sensor	CMOS
Chip size	1/2,8"
Flickerless function	Yes

MPC-52C0000M0B

Camera shape	Box
Signal-to-noise ratio	50 dB
Day/night mode	Automatic, Day,Night, extern (Sensor)
White balance	Automatic, Preset, Manual, AUTOext
Photosensitivity	0.005Lux @F1,6 (Day mode),0.0005Lux(Night mode)
System	True Day&Night
Day/night switching	Switchable IR Filter (ICR)
Functions	
Digital Noise Reduction (DNR)	Yes
Menu languages	Chinese, English, French, German, Japanese, Korean
Notes	
Remark	NDA compliance under Section 889
Interfaces / Inputs/ Outputs	
Alarm inputs	0
Number of alarm outputs	0
External connections	voltage input, 1x SDI Signal (BNC), 1x HD/SD Analog Signal (BNC)
Interface Protocols	UTC (HD Signal Format)
Control Interfaces	Coaxitron (HD Protocol)
Parts supplied	
Scope of delivery	manual, C/CS adapter
Video	
Signal Format	AHD @ 2MP, Composite (FBAS), EX-SDI @ 2MP, HD-SDI @ 2MP, HD-TVI @ 2MP
Product labeling:	
Manufacturer order number	243655
Series	eneo KX-Serie,eneo COAXIZE

Optional Accessory



F02Z2.8DC-NFSHD
2.8-12mm



F03Z06NDDC-MP
8-50mm



VIU-20

