MPD-62M2713P0B

243652



HD Analogue Dome Fixed, WDR, Day&Night,
2.7-13,5mm, Infrare 1920x1080, 12VDC, Indoor

Main Features

- 1/2.8" 2 Megapixel SONY STARVIS 2 CMOS sensor
- Resolution max. 1920x1080 pixels (Full HD)
- Super low light performance by Sony STARVIS 2 technology
- Multisignal: HD-TVI, AHD, CVI and Composite selectable
- Digital signal: EX-SDI, HD-SDI selectable
- Motorized vari-focal lens 2.7~13.5mm
- Removable infrared cut filter
- ROI (Region of Interest) WDR mode
- Integrated motion detector, defog, privacy zones
- Wedge adapter included (10° inclination)
- Scratch resistant hard coated bubble
- Easy installation, 3-Axis gimbal

Specifications

General	
Lighting	Infrared
Dimensions (WxHxD) (extended)	94x116mm
Illumination range	ca. 30m
Weight	0.26 kg
Text overlay	available
Color (Housing)	white
Housing type	Inside
Housing material	Plastic
Power consumption	6 W
Mounting type	Ceiling, Wall

© Copyright eneo by VIDEOR E. Hartig GmbH, November 4, 2026 -Technical changes reserved

MPD-62M2713P0B

Power supply	12VDC
Temperature Range (Operating)	-10°C ~ +50°C
Wide Dynamic Range (WDR)	D-WDR
Camera	
Backlight compensation	Yes
Low Speed Shutter	Yes
Recording sensor	CMOS
Chip size	1/2,8"
Flickerless function	Yes
Camera shape	Minsters
Signal-to-noise ratio	50 dB
Day/night mode	Automatic,Day,Night,extern (Sensor)
White balance	Automatic,Preset,Manual,AUTOext
Photosensitivity	0.005Lux(Day mode),0.0005Lux(Night mode)
System	True Day&Night
Day/night switching	Switchable IR Filter (ICR)
Display	
Image resolution max.	1920x1080
DORI	
Watch (62px/m)	18 - 52 m
Detect (125px/m)	8 - 25 m
Identify (250px/m)	4 - 12 m
Perceiving (25px/m)	47 - 128 m
Functions	
Motion detector	Yes
Digital Noise Reduction (DNR)	Yes
Menu languages	Chinese, English, French, German, Japanese, Korean
Notes	
Remark	NDAA compliance under Section 889
Interfaces / Inputs/ Outputs	
External connections	voltage input,1x SDI Signal (BNC),1x HD/SD Analog Signal (BNC),connection cable approx.15cm
Interface Protocols	UTC (HD Signal Format)
Control Interfaces	Coaxitron (HD Protocol)
Video Outputs	AHD, Composite (FBAS)
Parts supplied	
Scope of delivery	Quick installation guide,drilling template,3x wall plugs with screws,video sub-output cable,flat and angled mounting adapters,universal tool
Lens	
Horizontal angle of view	101 - 32°
Vertical angle of view	54 - 18°

© Copyright eneo by VIDEOR E. Hartig GmbH, November 4, 2026 -Technical changes reserved

MPD-62M2713P0B

Focal length	2,7 - 13,5 mm
Aperture Range (F)	F1.6
Lens Type	Varifocal (motorized)
Zoom Factor (Digital)	0
Zoomfactor (optical)	4
Video	
Resolution (extended)	1920x1080,1280x720,720x576
Signal Format	AHD @ 2MP, Composite (FBAS), HD-TVI @ 2MP
Product labeling:	
EAN/GTIN	4260229841365
Manufacturer order number	243652
Series	eneo COAXIZE

© Copyright eneo by VIDEOR E. Hartig GmbH, November 4, 2026 -Technical changes reserved