



VS10WGF

10.4" Metal Frame TFT LCD Monitor

Viewing Area	10.4"
Touch Panel	(optional)
Pixel Pitch	0.264 X 0.264 mm
Resolution	800 X 600 SVGA
Response Time(tr/ta)	10/25ms
Contrast Ratio	500:1
Brightness	230 cd/m ²
View Angle	T:35° B:65° L:60° R:60°
Backlight	1 CCFL
Lamp Life	20000 hrs
Input Signal	Analog VGA & Video (CVBS PAL/NTSC/SECAM)
Input Connector	D-Sub 15Pin / BNC Jack, S-VHS Din Type
Scan Frequency	H: 31.5~48KHz / V: 56~75Hz
Control	OSD
Input & Output	Universal AC 100~240 V, 50/60Hz & DC12V
Power Input	Terminal Block Input DC 12V +/-5%
Power Management	VESA DPMS Standard
Consumption	12W / Stand by 1W
Operating Temperature/Humidity	0 ~ 50°C / 10 ~ 85%RH
Storage Temperature/Humidity	-20 ~ 60°C / 10 ~ 90%RH
Sync Signal	TTL Level +/- Polarity
Scanning	Non-Interlace
Dimension (mm) (WxHxD)	270 x 200 x 59
Net Weight (Kg)	2.3
Safety & EMI	CE (EMC+LVD) / FCC
Vibration	10Hz / One-way 1m/m
Pixel (MHz)	50 MHz
Content	LCD Monitor, Key Pad, Power Adaptor, VGA Cable

specification subject to change without notice

Optional accessories

Rackmount bracket	Option
Stand Base Unit	Option